

**ОТКРЫТОЕ АКЦИОНЕРНОЕ ОБЩЕСТВО
СЛОНИМСКИЙ КАРТОННО-БУМАЖНЫЙ ЗАВОД**



Беларусь

231793, Гродненской обл., г. Слоним
ул. Фабричная, 1
Телетайп 194572
Телефакс (8-01562) 3-20-56
Телефоны: директор 3-20-58, 3-13-97
маркетинг 3-14-40, 3-23-44
сбыт 3-20-55, 3-13-08
снабжение 3-20-59, 3-15-78
Адрес электронной почты: marketing@albertin.by
Сайт: www.albertin.by

Belarus

231793, Grodno region, Slonim
Fabrichnaya Str., 1
Teletype 194572
Fax (8-01562) 3-20-56
Telephones: director 3-20-58, 3-13-97
marketing 3-14-40, 3-23-44
sales 3-20-55, 3-13-08
supply 3-20-59, 3-15-78
E-mail: marketing@albertin.by
Website: www.albertin.by

№ _____
На _____ от _____

Commercial proposal

Joint-stock company «Slonim cardboard and paper plant «Albertin» is one of the largest enterprises of the paper industry in Belarus. Products with the brand name "Albertin" is widely known both in domestic and foreign markets. We offer more than 120 kinds of goods. Basic goods sold for export:

Cardboard - polygraphic, cardboard for box production, coreboard, linerboard.

Paper- packaging, paraffined paper, corrugating paper.

Products sanitation supplies - toilet paper, paper towels, napkins.

231793 Grodno region, Slonim, Fabrichnaya Str., 1

Tel./fax + 375 156232344; e-mail: marketing@albertin.by; website: www.albertin.by

№ r/n	Name of goods	Code TN VED EurAzES	Format, mm	Price in Euro per 1 ton on terms FCA Slonim
1.	Cardboard mark «KG» reeled. Thickness: 0,60 - 0,80 mm. It is intended for the manufacturing of cores. The cores are used to wrap various roll products such as paper, cardboard, rubber, cellophane and other materials. The trimmed width of the board machine is 1780 mm. 100% recycled fibers.	4805 93 200 0	On the basis of the full trimmed width of the machine 1780 mm	310
2.	Water-resistant cardboard for box production mark «KT» Thickness: 0,80 mm - reeled	4805 93 200 0	On the basis of the full trimmed width of the machine 1780 mm	370

	Water-resistant cardboard for box production mark «KT» Thickness: 0,80 mm - in the flat Standard sheet-740x1050 mm.	4805 93 200 0		390
3.	Linerboard "K-3" reeled. It is used for producing corrugated board. Paper density 125, 140, 150, 175 g/m ² , painted.	4805 24 000 0	On the basis of the full trimmed width of the machine 2520 mm	325
4.	Corrugating paper. It is used as corrugated board's layer. «B-2». Mark «B-2», density 90,100, 112, 125 g/m ² .	4805 19 900 0	On the basis of the full trimmed width of the machine 2520 mm	320
5.	Corrugating paper. It is used as corrugated board's layer. «B-3». Mark «B-3», density 100, 112, 125 g/m ² .	4805 19 900 0	On the basis of the full trimmed width of the machine 2520 mm	310

- The goods quality is proved by the quality control system corresponding to the requirement of international standard ISO -9001-2009.
- The terms of delivery: minimal lot of goods – 20 tons. Truck and rail shipment.

All technical characteristics of the paper and the board you can find on website www.albertin.by

Best regards,
General Director

N. V. Antonik